



# ZT 4 KIT MONACO



Suitable for residential and condominium use with wing width up to 3 m.

Maximum reliability thanks to the sturdiness of the operator.

Anti-crush system with very sensitive bypass valves calibrated during installation. This immediately cuts the hydraulic pressure in the event of obstacles to ensure maximum system safety.

## TECHNICAL DETAILS

Front and rear mountings to enable screw assembly also on wood, PVC and aluminium gates.

Manual key release located on the upper part of the operator in the event of mains power supply failure.

The articulated fork rear flange ensures flexible and sturdy assembly on the pillar.

The neoprene power supply cable is specifically suited to mobile applications in outdoor environments.

TECHNICAL DATA	ZT 4
VERSIONS	C SF
KEY RELEASE	YES
NUMBER OF CYCLES	55 cycles/hour
MAX. WING WIDTH	3.0 m (SF) - 1.8 m (C)
ANTI-CRUSH SYSTEM	YES
STANDARD MAX. ROD STROKE	275 mm
ROD ENTRY TIME	17 SEC
ROD EXIT TIME	21 SEC
POWER ABSORBED	250 W
MAX. THRUST FORCE	3850 N
OPERATING TEMPERATURE	-20°/+70° C
OVERLOAD TEMPERATURE	120° C
PROTECTION RATING	IP 55

